



Ftan

PERSON:
Julian, Jarek, Lukas, Michael, Christian, Stefan
PIERRE: Axel, Subhayan
EVENTS: Max, Markus, Lucas
STATISTICS: Dominik, Uwe, M. Tsch

Kreis 1/16

Kreis 2/16

1)

NE part

NE (3 sides) part

statisches

Dominik

Uwe, M. Tsch

base complete
and XML and HTML in all cases
should be with DTD
however very common often
and fast memory access

SETTEI
Information about the system
and its components



FtanML

reinventing markup

MICHAEL KAY

- FtanML
 - The document markup language
- FtanGram
 - The schema language
- FtanSkrit
 - The scripting language

FtanML Example

```
<Polygon  
filled=true  
color="blue"  
corners=[[1,0], [1,1], [0,1], [0,0]]  
lineWidth=0.5  
label=|You are <i>so</i> square!|>
```

FtanML Constructs

Elements

RichText

Numbers

Booleans

Strings

Lists

Null

Functions

Strings

"Max Weber"

'abcde\
fghijk'

"\xA0;"

'\r\n'

"He said \"I'm not\""

Escapes

- Special characters: \<, \\, \", ...
- Whitespace: \s, \n, \t, \r, \S (=nbsp)
- Ignored whitespace: _____
- Hex Unicode codepoints: \x13a0f;
- Cells: \[♦qwertyuiop♦]

Lists

[]

["red", "green", "blue"]

[3,null]

[[1,0], [1,1]]

[<a>, , <c>]

["red", 1, true]

Elements

- Optional name (any string)
- Zero or more attributes
 - Name (any string)
 - Value (any value)
- Optional content
 - Any value

Element examples

<>

<a>

<*>

<div [<p><p>]>

<x=3 y=4 z=null> <'AT&T'=23.5>

<title |this is FtanML|>

<from=[0,1] to=[1,1]>


Namespaces

THERE ARE NO NAMESPACES.

Rich Text

```
<para |Drink lots of \  
<chem |H<sub>2</sub>O|>|  
|>
```

Data Model



What about nodes?

THERE ARE NO NODES.

VALUES HAVE NO IDENTITY (ONLY EQUALITY).

THERE ARE NO PARENT POINTERS.

Whitespace?

SIGNIFICANT IN STRINGS AND TEXT.

IN SIGNIFICANT EVERYWHERE ELSE.

FtanGram

The schema language for FtanML

To grasp this sorry Scheme of Things entire, and ...
re-mould it nearer to the Heart's Desire

FtanGram Types

- A schema is a set of (named) types
- A type has a FtanML representation as an element
- A type is a predicate
- There is no overt type hierarchy

Some types



```
<number ge=0 le=100 step=0.01>  
<string pattern="[A-Z][0-9]">  
<enum=["a", "b", "c", "d"]>  
<assert={$@end > $@start}>
```

Composing Types

<allOf [<t1>, <t2>]>

<anyOf [<t1>, <t2>]>

<not <t1>>

<nullable <t1>>

Grammars

```
<list grammar=
  <number occurs=[1,]>>
```

```
<list grammar=
  <seq [<number>,
        <string>,
        <boolean occurs=[1,5]>]>>
```

Particles

- A grammar is a particle
- A particle is an occurrence indicator plus one of:
 - <seq> + a list of particles
 - <choice> + a list of particles
 - a type

Element Proformas

```
<element form=
  <e x=<number>
    y=<number>
    z=<nullable<number>>>
```

> >

Schema

```
<schema  
percentage = <number ge=0 le=100>  
zipcode = <string pattern="\[=\d{5}\]">  
emps = <list grammar=  
           <emp occurs=[0,]>>  
emp = <element form=  
           <emp first=<string>  
               last=<string>  
               bonus=<percentage>>  
           >  
>
```

FtanSkrīt

The scripting language for FtanML

Variables

```
let x=3; let y=[4,5]; x+y[1]
```

Functions

```
let add={$1+$2};  
add(2, 2)
```

```
let x=5;  
let up={$+x};  
7.up0
```

Filter>Select

```
let a = 1..100;  
a?{$.mod(2) = 0}
```

```
emps?{@salary > 50000}
```

```
let married = {@status='M'};  
emps?married
```

Map/Apply

```
let a = 1..100;  
a!{$*2}
```

```
max(emps!{@salary})
```

```
let age = {today().yearsSince(@dob)};  
avg(emps!age)
```

Operations on Types

a.isA(<percentage>)

a.as(<percentage>)

Operations on Lists

```
let a = 1 ~+ 2..5 ++ [6,7,8,9] +~ 10  
a = [1,2,3,4,5,6,7,8,9,10]
```

a[0] = 1

count(a) = 10

Operations on Elements

```
let n = 3;
```

```
let a = <e x=(n+1) y=(n+2)>;
```

```
a@x
```

```
<e>.add("x",2).add("y",3)
```

Implementation

<https://github.com/FtanML-WG/Scala-Parser>

Questions?

